

Block 37

Chicago, Illinois

Keller met the challenges of this complex and fast-tracked project utilizing drilled shaft, slurry, and secant wall techniques.



The project

Block 37 was to be repurposed as a shopping, dining, entertainment destination in the downtown district of Chicago. Access to the local Chicago Transit Authority (CTA) line was also needed.

The challenge

Existing below-grade structures and demolition debris from the previous building made for difficult site excavation. Local CTA services also remained active outside the property line.

The solution

New caissons were designed to work around any obstructions during construction. Keller installed 65,000 square feet of 36-inch thick slurry wall to surround the four-level underground parking garage and also provide access for a new CTA Subway line. Secant pile walls, in selected sections, protected adjacent streets and structures from damage. Both rock and hardpan drilled shafts supported the high-rise structures. Finally, structural steel column sections, placed in selected drilled shafts, enabled the top-down construction program to proceed.

Project facts

Owner(s)

Bank of America

Keller business unit(s)

Keller

Main contractor(s)

W.E. O'Neil

Engineer(s)

Thornton Tomasetti

Solutions

Deep foundations

Markets

Commercial

Techniques

Drilled shafts

Secant or tangent (contiguous) piles

Diaphragm walls

Email address

info@keller-na.com

Phone number

1 (800) 456-6548