

Red Rock Hydroelectric

Pella, Iowa

Slurry walls addressed multiple design and dam safety aspects on this challenging project.



The project

The Red Rock Hydroelectric Project, located at the existing U.S Army Corps of Engineers Red Rock Dam, in central lowa near the city of Pella, involved the construction of a new intake, water conduits, powerhouse, transmission facilities, utilities, and appurtenances. The dam is a composite earth fill and concrete gravity structure, used for flood control and recreation.

The challenge

Challenges included a very tight job site and working through the winter months to meet the schedule.

The solution

Keller installed a reinforced concrete diaphragm wall along the approach channel, intake structure, and upstream penstocks; a seepage cutoff wall parallel to the dam crest alignment; a secant piles cofferdam to facilitate construction of the permanent intake structure upstream of the existing dam; anchored secant piles wall around powerhouse excavation, downstream of the existing dam; drilled shaft foundations for the new Intake Structure and Penstocks.

The diaphragm walls were constructed by Keller, using bentonite slurry as trench support, a primarysecondary element scheme, and a BC-40 Hydromill as the major excavation tool. The heavily reinforced upstream diaphragm wall consisted of 26 large T-shaped panels (approximately 68,328 SF), 135 feet deep including a 35-foot rock socket and a 5-foot thickness. Its primary purpose was to retain the upstream dam embankment and form the left side of the intake approach channel. Reinforcement cages weighed up to 100 tons each. The diaphragm cutoff wall along the dam crest addressed potential seepage and dam safety concerns. It consisted of 10 panels (8,850 square feet), with depths of 86 feet.

Project facts

Owner(s) Western Minnesota MunicipalPower Agency

Keller business unit(s) Keller

Main contractor(s) Ames Construction, Inc.

Engineer(s) MWH Americas, Inc.

Solutions

Support of excavation Deep foundations Groundwater control and dewatering

Markets

Infrastructure Dams and levees Power

Techniques

Diaphragm walls Drilled shafts Slurry cutoff walls Secant or tangent (contiguous) piles

Email address info@keller-na.com

Phone number 1 (800) 456-6548