

## Thornton Tunnel Grouting

Thornton, Illinois

Keller's tunnel grouting ensured continuity of the grout curtain around the 7.8 Billion Gallon CSO (combined sewage overflow) storage reservoir.



### The project

The Thornton Composite Reservoir Project included a 30-ft diameter connecting tunnel from the reservoir to the existing Calumet Deep Tunnel, a 20-ft diameter connecting tunnel from the reservoir to the Thorn Creek Diversion Tunnel and two abandoned mining haul tunnels. Grouting was required to create cut-off rings to reduce groundwater movement along the exterior of the tunnels and to tie into the double-row grout curtain around the reservoir.

## The challenge

Keller was contracted to reduce the permeability of the bedrock to an approximate value of 1 Lugeon by drilling and grouting from inside the tunnels (tunnel grouting) in a 360-degree ring pattern, drilling holes with strict alignment requirements, and injecting a suite of balanced and stable grouts in multiple stages overhead.

## The solution

Keller used upstage and downstage techniques to complete the ring drilling and grouting operation. The grout hole lengths varied from 10 to 40 feet and were drilled with compact, limited access drills.

## Project facts

### Owner(s)

Metropolitan Water Reclamation District of Greater Chicago

### Keller business unit(s)

Keller

### Main contractor(s)

F.H. Paschen  
Walsh Construction Company

### Engineer(s)

Black & Veatch and MWH Americas

### Solutions

Groundwater control and dewatering

### Markets

Infrastructure  
Water, sewage and waste disposal

### Techniques

High mobility (cement slurry) grouting

### Email address

[info@keller-na.com](mailto:info@keller-na.com)

### Phone number

1 (800) 456-6548